



Technical data sheet

Air separator

Air separator made from black steel tube P235. With two welded ends and a ½" ventilation bushing. For either vertical or horizontal installation. The air separator is 100% tightness tested and primed before leaving the factory.

Manufacturer certification	
Description	Air separator
Design pressure	up to 6 bar
Design temperature	0/+110 °C
Design procedure	Article 4, Paragraph 3
Manufacturer	Sinusverteiler GmbH Dieselweg 2 48493 Wettringen/Germany

We declare under our sole responsibility that the pressure equipment meets the requirements of Directive 2014/68/EU. This product was manufactured in accordance with the principles of GEP "Good Engineering Practice".

	Size	Nozzle (A)	Length (L)	Capacity
	[DN]	[DN]	[mm]	[litres]
for vertical installation 	65	25	250	0.8
	80	32	250	1.2
	100	40	250	2.5
	125	50	300	3.7
	150	65	300	5.5
	200	80	500	15.7
	250	100	500	24.5
	300	125	500	34.4
	350	150	600	50.6
	400	200	700	77.7
for horizontal installation 	65	25	250	0.8
	80	32	250	1.2
	100	40	250	2.5
	125	50	300	3.7
	150	65	300	5.5
	200	80	500	15.7
	250	100	500	24.5
	300	125	500	34.4
	350	150	600	50.6
	400	200	700	77.7