



Technical data sheet

Air trap with threaded connection

Air trap with threaded connection made from black sheet steel P235. With two nozzles (internal thread) and a ½" ventilation bushing. For either vertical or horizontal installation. The air trap with threaded connection is 100% tightness tested and primed before leaving the factory.

| Manufacturer certification | |
|----------------------------|--|
| Description | Air trap with threaded connection |
| Design pressure | up to 6 bar |
| Design temperature | 0/+110 °C |
| Design procedure | Article 4, Paragraph 3 |
| Manufacturer | Sinusverteiler GmbH Dieselweg 2 48493 Wettringen/Germany |

We declare under our sole responsibility that the pressure equipment meets the requirements of Directive 2014/68/EU. This product was manufactured in accordance with the principles of GEP "Good Engineering Practice".

| | Size | Length (L) | Capacity | Nozzle |
|--|------|------------|----------|----------------------|
| | [DN] | [mm] | [litres] | [inches] |
| for vertical installation  | 65 | 250 | 0.8 | 1", internal thread |
| | 80 | 250 | 1.2 | 1¼", internal thread |
| | 100 | 300 | 2.5 | 1½", internal thread |
| | 125 | 300 | 3.7 | 2", internal thread |
| for horizontal installation  | 65 | 250 | 0.8 | 1", internal thread |
| | 80 | 250 | 1.2 | 1¼", internal thread |
| | 100 | 300 | 2.5 | 1½", internal thread |
| | 125 | 300 | 3.7 | 2", internal thread |