

Technical data sheet

Maintenance box for magnetite separation

The maintenance box as an optional accessory for magnetite separation. Made from black sheet steel S235 profile tubing. Equipped with sludge removal nozzle and ball valve 1/2" as well as a magnetite bar screwed into a thermowell. To be attached to the boiler return beneath the manifold. Enables sludge removal in pressurised systems.

Manufacturer certification

Description	Maintenance box for magnetite separation
Design pressure	4 bar
Design temperature	0/+110 °C
Design procedure	Article 4, Paragraph 3
Manufacturer	Sinusverteiler GmbH Dieselweg 2 48493 Wettringen/Germany

We declare under our sole responsibility that the pressure equipment meets the requirements of Directive 2014/68/EU. This product was manufactured in accordance with the principles of GEP "Good Engineering Practice".

Type	Suitable for	Heating water flow rate	Connection A	Connection B	Wall thickness
[WxH]		[m³/h]	[inches]	[inches]	[mm]
80/60	Small manifold 80/60 HydroFixx 80/80 MonoFixx 80/80	3.0	1 1/2" union nut	1 1/2" union nut	3
120/80	Small manifold 120/80 HydroFixx 120/120 MonoFixx 120/80	7.0	2" internal thread	2" external thread	3

